

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) A vehicle, comprising:  
    ~~a tag, said tag~~ first and second tags being mounted in the vehicle, ~~the tag~~ each of the tags including a recording medium in which identification information for identifying the vehicle is registered,  
    wherein the ~~tag is~~ tags are attached inside a vehicle seat to be sat on by a user in the vehicle, said vehicle seat being composed of a resin member,  
    wherein the vehicle seat is a primary vehicle seat that is directly attached the vehicle,  
    and  
    wherein the first tag is located adjacent to a front of the seat and ~~or rear~~ the second tag is located adjacent to a rear of the seat so that a distance between the first tag and an outside of the front of the seat is small, and a distance between the second tag and an outside of the rear of the seat is small, such that the identification information of the vehicle can be obtained via a tag reader placed near either the first tag or the second tag attached inside the primary vehicle seat.
2. (Canceled).
3. (Original) The vehicle according to claim 1, wherein the vehicle is a saddle-type vehicle.
- 4-6. (Canceled).
7. (Currently Amended) The vehicle according to claim 1, wherein ~~the tag~~ each of the tags is an RFID tag including an IC and means for transmitting/receiving radio signal embedded therein.

8. (Canceled).

9. (Currently Amended) A vehicle, comprising:

a vehicle body;

a vehicle seat composed of a resin member attached to said vehicle body, said vehicle seat to be sat on by a user in the vehicle; and

a tag and a second tag each of which is attached inside said resin member of said vehicle seat, ~~said tag~~ said tags including a recording medium in which identification information for identifying the vehicle is registered,

wherein the vehicle seat is a primary vehicle seat that is directly attached the vehicle, and

wherein the first tag is located adjacent to a front of the seat and the second tag is located adjacent to a rear ~~or rear~~ of the seat so that a distance between the first tag and an outside of the front of the seat is small, and a distance between the second tag and the rear of the seat is small, such that the identification information of the vehicle can be obtained via a tag reader placed near either the first tag or the second tag attached inside the primary vehicle seat.

10. (Canceled).

11. (Original) The vehicle according to claim 9, wherein the vehicle is a saddle-type vehicle.

12-14. (Canceled).

15. (Currently Amended) The vehicle according to claim 9, wherein ~~the tag~~ each of the tags is an RFID tag including an IC and means for transmitting/receiving radio signal

embedded therein.

16. (Canceled).

17. (Currently Amended) A resin member for a vehicle, comprising:

~~a tag, said tag~~ first and second tags being attached inside the resin member, ~~said tag~~ each of said tags including a recording medium in which identification information for identifying the vehicle is registered,

wherein the resin member is a vehicle seat to be sat on by a user in the vehicle,

wherein the vehicle seat is a primary vehicle seat that is directly attached the vehicle,

and

wherein the first tag is located adjacent to a front of the seat and the second tag is located adjacent to a rear ~~or rear~~ of the seat so that a distance between the first tag and an outside of the front of the seat is small, and a distance between the second tag and the rear of the seat is small, such that the identification information of the vehicle can be obtained via a tag reader placed near either the first tag or the second tag attached inside the primary vehicle seat.

18. (Canceled).

19. (Canceled).

20. (Currently Amended) The resin member according to claim 17, wherein ~~the tag~~ each of the tags is an RFID tag including an IC and means for transmitting/receiving radio signal embedded therein.

21. (Canceled).

22. (Currently Amended) A vehicle according to claim 1, wherein the vehicle seat includes an internal member extending between the front side and the rear side of the vehicle seat,

wherein a front side of the internal member faces substantially in a forward direction, and a rear side of the internal member faces substantially in a rearward direction,

wherein the first tag is disposed on the front side of the internal member, and

wherein the second tag is disposed on the rear side of the internal member.

~~the tag includes:~~

~~at least two tags attached inside the vehicle seat, each of the tags including the recording medium in which identification information for identifying the vehicle is registered,~~

~~wherein a first one of the tags is located adjacent to the front of the seat that is directly attached the vehicle so that a distance between the tag and the front of the seat is small such that the identification information of the vehicle can be obtained via a tag reader placed near the first tag, and~~

~~wherein a second one of the tags is located adjacent to the rear of the seat that is directly attached the vehicle so that a distance between the second tag and the rear of the seat is small such that the identification information of the vehicle can be obtained via the tag reader placed near the second tag.~~

23. (Currently Amended) A vehicle according to claim 9, ~~wherein the tag includes:~~

~~at least two tags attached inside said resin member of said vehicle seat, each of said tags including the recording medium in which identification information for identifying the~~

~~vehicle is registered,~~

wherein the vehicle seat includes an internal member extending between the front side and the rear side of the vehicle seat, wherein a front side of the internal member faces substantially in a forward direction, and a rear side of the internal member faces substantially in a rearward direction,

~~wherein a first one of the tags~~ the first tag is disposed on the front side of the internal member ~~so that a distance between the first tag and a forward side of a seat surface of the vehicle seat is small such that the identification information of the vehicle can be obtained via a tag reader placed near the first tag, and~~

~~wherein a second one of the tags~~ the second tag is disposed on the rear side of the internal member. ~~so that a distance between the second tag and a rear side of the seat surface of the vehicle seat is small such that the identification information of the vehicle can be obtained via the tag reader placed near the second tag.~~

24. (Currently Amended) A resin member for a vehicle according to claim 17, wherein the vehicle seat includes an internal member extending between the front side and the rear side of the vehicle seat,

wherein a front side of the internal member faces substantially in a forward direction, and a rear side of the internal member faces substantially in a rearward direction,

wherein the first tag is disposed on the front side of the internal member, and

wherein the second tag is disposed on the rear side of the internal member.

~~the tag includes:~~

~~multiple tags attached inside the resin member, each of said tags including the recording medium in which identification information for identifying the vehicle is registered,~~

~~wherein a first one of the tags is located adjacent to a front facing portion of a seat surface of the vehicle seat so that a distance between the first tag and the front facing portion~~

~~of the seat surface is small such that the identification information of the vehicle can be obtained via a tag reader placed near the first tag, and~~

~~wherein a second one of the tags is located adjacent to a rear facing portion of the seat surface the vehicle seat so that a distance between the second tag and the rear facing portion of the seat surface is small such that the identification information of the vehicle can be obtained via the tag reader placed near the second tag.~~

25. (Currently Amended) The vehicle according to ~~claim 22~~ claim 1, wherein each of the first tag and the second tag is aligned in a direction that is substantially orthogonal to a portion of a seat surface of the seat to be sat on by the user of the vehicle.

26. (Currently Amended) The vehicle according to ~~claim 23~~ claim 9, wherein each of the first tag and the second tag is aligned in a direction that is substantially orthogonal to a portion of a seat surface of the seat to be sat on by the user of the vehicle.

27. (Currently Amended) The resin member according to ~~claim 24~~ claim 17, wherein each of the first tag and the second tag is aligned in a direction that is substantially orthogonal to a portion of the seat surface of the seat to be sat on by the user of the vehicle.